



Channelline i

Advantages

- ▶ High-quality recessed/surface-mounted profile
- ▶ Almost rimless illuminated surface
- ▶ For flush mounting
- ▶ Filigree profile for thin materials

Features

- ▶ New opal cover - 30% more light and only slight change in light colour
- ▶ Homogeneous light line with Versa Inside from 233 LED/m
- ▶ Very wide beam angle of approx. 100°

Examples of use

- ▶ Flush with cabinet sides or shelves
- ▶ Retrofitting in niches

Order information

- ▶ For selection see Channelline overview

Technical details



Recommended for:

Versa Inside 233 HP
Versa Linear



Channelline i

	Alu/Opal	Black/Opal	Black / Black
2000 mm	55 874 01	55 874 05	55 874 07
2000 mm (set of 10)	55 874 11	55 874 15	55 874 17
3000 mm	55 874 02	55 874 06	55 874 08
3000 mm (set of 10)	55 874 12	55 874 16	55 874 18
End cap (set of 2) lacquered	25 563 01	25 563 05	25 563 05
Sample piece profile 300 mm	50 021 01	50 022 01	50 022 01
Sample piece cover 300 mm	50 026 01	50 026 01	50 028 01
Cleaning cloth (isopropanol)	36 502 01	36 502 01	36 502 01

Dimensional drawing / installation

