



Versa Linear

Advantages

- ▶ Extremely uniform, homogeneous luminous surface
- ▶ Equally suited for unctonal and accent lighting
- ▶ Perfect results even in flat profiles

Features

- ▶ Homogeneous illumination in Channelline profiles
- ▶ For 3000 mm length power supply from two sides (one cut, two lights), see drawing
- ▶ COB (Chip-On-Board) with continuous phosphor coating

Examples of use

- ▶ Especially for flat Channelline profiles
- ▶ Ideal for Channelline I, I2 and M
- ▶ Suitable for applications where the light source is visible e.g. frame lighting on mirror cabinet

Order information

- ▶ Soldering leads are required for the 10 m roll
- ▶ Colour uniformity (chromaticity) may vary
- ▶ For selection see Versa- and Channelline Overview

Technical details



Luminaire type: Surface-mounted light
 Type of lighting: Function lighting/ Accent lighting
 Operating voltage: 12 V DC
 Light colours: XtraWarmWhite/ WarmWhite/ NeutralWhite
 Colour rendering: RA >90; R9 >60
 Luminous flux: 1000 lm/m
 Light source efficiency: 100 lm/W
 Life span: 40,000 h (L70)
 Power consumption: 10 W/m
 Max. length at a stretch: 3.6 m
 Dimmable: Yes/PWM/Smart.home
 Number of LEDs: 120/m
 Beam angle: 120°
 Half value angle: 70°
 Test mark and symbols: CE, RoHS, Energy Star
 Protection rating: IP 20
 Supply lead: 1800 mm
 Plug connector: LED mini connector M1 (max. 36 W)
 Connection to: LED ballast

Versa Linear (COB technology)

	XtraWarm	WarmWhite	NeutralWhite
1200 mm (max. 12 W)	56 009 42	56 009 12	56 009 02
3000 mm (max. 30 W)	56 009 43	56 009 13	56 009 03
10000 mm (max. 10 W/m)	56 009 41	56 009 11	56 009 01

Accessories*

	1 piece	10 piece
Direct connector COB	36 358 01	36 358 11
Flexible connector 50 mm COB	36 359 01	36 359 11
Flexible connector 150 mm COB	36 360 01	36 360 11
Feeder 1800 mm for sections COB	36 361 01	-
Soldering lead 130 mm for sections (max. 72 W)	39 297 38	-
Soldering lead 1800 mm for sections (max. 72 W)	36 248 01	-
LED ballast 15 W with flat Euro plug	30 996 17	-
LED ballast 30 W with flat Euro plug	31 002 07	-
M1 extension lead 1800 mm	36 768 01	-
M1 3-way distributor 180 mm	36 852 01	-

* Further accessories in section Switch systems

Dimensional drawing / installation

